

QWIK[®] **SENSOR** *TPMS MULTIPACKS*

QWIK-SENSOR[®] IS NOW AVAILABLE IN MULTIPACKS OF 25

TPM9025

Includes 25 of the QS106R
Multi-Frequency QWIK-SENSORS[®]
with rubber valve stems



TPM9026

Includes 25 of the QS106M
Multi-Frequency QWIK-SENSORS[®]
with metal valve stems



- Saves technicians' time by having programmable sensors on-hand
- For use on import and domestic applications
- Available with rubber or metal valve stems
- Individually packaged and protected sensors



QWIK-SENSOR[®] 315/433 MHz MULTI-FREQUENCY TPMS SENSOR



QS106M

With factory-installed aluminum valve stem



QS106R

With factory-installed rubber valve stem

Required sensor programming can be completed before or after installation and while under pressure

Application Specific Integrated Circuit (ASIC) features an accelerometer that uses multi-axis positioning which allows the TPMS system to accurately display POD (Pressure on Demand)

Surface-mounted dual-band antenna enhances signal integrity and reliability without compromising battery life to ensure data is transmitted accurately

Independently tested to match OE protocols for precise form, fit and function – including LOCSYNC, PAL, POD, and WAL advanced TPMS technologies

Available for both domestic and import applications with 314.9MHz - 434MHz TPMS systems

